



Technical Data Sheet

SISTA PREMIUM VINYL TILE ADHESIVE

Flooring Adhesive for Vinyl Tile

Product description:

SISTA Premium Vinyl Tile Adhesive is a special grade of acrylic emulsion for flooring adhesive. It is high performance for installing PVC tile and homogeneous & heterogeneous vinyl flooring tile. It has good tack, good adhesion, good moisture resistant, good alkali-resistant, non-shrinkage and long durability.

SISTA Premium Vinyl Tile Adhesive is plasticizer free, low volatile organic content and low odor.

Characteristics:

- Good adhesion for all types of vinyl flooring tile (Roll & sheet)
- High tackiness
- Non shrinkage and long durability
- Can apply both pressure sensitive bonding and semi-wet bonding
- Low VOC follow ISO 11890-2

Technical data:

- | | |
|--------------------|------------------|
| - Color | White |
| - Solid content | approx. 53% |
| - pH | 7.5 – 8.5 |
| - Specific gravity | 1.15 – 1.20 g/ml |

Field of application:

- Can use for all type of vinyl tile (Roll & sheet)
- Can use for homogeneous and heterogeneous of vinyl tile
- Can apply on the existing and new concrete floors
- Suitable for indoor application

Application instruction:

- Floor must be smooth, clean, dry and free from dust, moisture, grease and wax.
- Floor substrate cracks, joints and uneven need to be fixed.
- Apply adhesive evenly to the floor using a notched trowel. Then leave the surface until adhesive is become tacky to touch or approximate 15 minutes (depend on temperature and type of floor substrate).
- Lay the flooring tiles on floor and pressed into place firmly. Firmly lay flooring tile by roller to perfectly install.
- Clean excess adhesive by clean cloth.
- Let SISTA Premium Vinyl Tile Adhesive completely dry at least 24 hours. Avoid heavy traffic for the first 7 days.

Packaging: Size 3 kg: 4 pieces / carton
Size 18 kg: Plastic drum

Storage: Close cap tightly after use and store in cool and dry place with
room temperature below 30°C.

Shelf life: 24 months

The above instructions are based on thorough trials and on general experience gained in this field. As it is impossible to survey all installation methods and in view of various different working conditions, we cannot, however, claim that the information given is complete. We therefore recommend that tests should be carried out on your own to ensure the greatest possible success. We guarantee a uniform quality standard for this product.

Henkel (Thailand) Ltd.
